



https://agking.com.au/product/90hp-tractor-ak904-air-conditioned-cabin/ https://www.youtube.com/watch?v=981R_f-kyR8





AK904 Cabin tractor from AgKing

AG King - AK904 air cabin, 90HP four cylinder YTO diesel engine, 4 Wheel Drive, with 12 speed forward and reverse gears, soft shuttle shift, diff lock, oil disc brakes, two sets of remote hydraulics, two speed hand control PTO, twin filter air intake, work lights, draw bar. Includes luxury cabin with air conditioning

Type Four wheel drive Length with FEL 6100mm Width 2180mm Height 2880mm Front wheel tread 1400mm Rear wheel tread 1300 - 1500mm Wheel base 2200mm Min ground clearance 405mm Weight with FEL + ballast 5100kg Engine model YTO LR4M5-23 Type 4 cyl, water cooled, 4 stroke Rated power 90hp (66.2kW) Rated speed 2200r/min Air filter double Fuel Diesel Fuel ank capacity 150L Clutch Dry-friction, 2 stage, ceramic disc Swing draw bar Yes (tow bar + swing draw bar) Cab Full view cabin with air con Steering power steering Gearbox 16F + 8R shuttle shift Max speed 33km/h Hydraulic output 2 sets rear remotes - 50L/min Suspension 3 point suspension, Cat 3 Lift capacity 2000kg (610mm behind hitch) Remote lift control lever for operator outside of cabin PTO shaft Non-independent type 540/760 r/min 135 Rectangle spline with 6 teeth Front End Loader Model AKS1500 Max lifting height 3710mm (at pivot pin) Dumping height 2720mm Overloading height 3490mm Ground clearance 1780mm Scraping depth 180mm Bucket width 2000mm Bucket capacity 0.7m3 Safe lifting weight 1500kg	AgKing AK904 Cabin	
Width 2180mm Height 2880mm Front wheel tread 1400mm Rear wheel tread 1300 - 1500mm Wheel base 2200mm Min ground clearance 405mm Weight with FEL + ballast 5100kg Engine model YTO LR4M5-23 Type 4 cyl, water cooled, 4 stroke Rated power 90hp (66.2kW) Rated speed 2200r/min Air filter double Fuel Diesel Fuel ank capacity 150L Clutch Dry-friction, 2 stage, ceramic disc Swing draw bar Yes (tow bar + swing draw bar) Cab Full view cabin with air con Steering power steering Gearbox 16F + 8R shuttle shift Max speed 33km/h Hydraulic output 2 sets rear remotes - 50L/min Suspension 3 point suspension, Cat 3 Lift capacity 2000kg (610mm behind hitch) Remote lift control lever for operator outside of cabin PTO shaft Non-independent type 540/760 r/min 135 Rec	Туре	Four wheel drive
Height 2880mm Front wheel tread 1400mm Rear wheel tread 1300 - 1500mm Wheel base 2200mm Min ground clearance 405mm Weight with FEL + ballast 5100kg Engine model YTO LR4M5-23 Type 4 cyl, water cooled, 4 stroke Rated power 90hp (66.2KW) Rated speed 2200r/min Air filter double Fuel Diesel Fuel tank capacity 150L Clutch Dry-friction, 2 stage, ceramic disc Swing draw bar Yes (tow bar + swing draw bar) Cab Full view cabin with air con Steering power steering Gearbox 16F + 8R shuttle shift Max speed 33km/h Hydraulic output 2 sets rear remotes - 50L/min Suspension 3 point suspension, Cat 3 Lift capacity 2000kg (610mm behind hitch) Remote lift control lever for operator outside of cabin PTO shaft Non-independent type 540/760 r/min I35 Rectangle spline with 6 teeth Front End Loader Model AKS1500 Max lifting height 3710mm (at pivot pin) Dumping height 2720mm Overloading height 3490mm Ground clearance 1780mm Scraping depth 180mm Bucket width 2000mm Bucket vidth 2000mm Bucket capacity 0.7m3	Length with FEL	6100mm
Front wheel tread 1400mm Rear wheel tread 1300 - 1500mm Wheel base 2200mm Min ground clearance 405mm Weight with FEL + ballast 5100kg Engine model YTO LR4M5-23 Type 4 cyl, water cooled, 4 stroke Rated power 90hp (66.2KW) Rated speed 2200r/min Air filter double Fuel Diesel Fuel tank capacity 150L Clutch Dry-friction, 2 stage, ceramic disc Swing draw bar Yes (tow bar + swing draw bar) Cab Full view cabin with air con Steering power steering Gearbox 16F + 8R shuttle shift Max speed 33km/h Hydraulic output 2 sets rear remotes - 50L/min Suspension 3 point suspension, Cat 3 Lift capacity 2000kg (610mm behind hitch) Remote lift control lever for operator outside of cabin PTO shaft Non-independent type 540/760 r/min 135 Rectangle spline with 6 teeth Front End Loader Model AKS1500 Max lifting height 3710mm (at pivot pin) Dumping height 2720mm Overloading height 3490mm Ground clearance 1780mm Scraping depth 180mm Bucket width 2000mm Bucket capacity 0.7m3	Width	2180mm
Rear wheel tread 1300 - 1500mm Wheel base 2200mm Min ground clearance 405mm Weight with FEL + ballast 5100kg Engine model YTO LR4M5-23 Type 4 cyl, water cooled, 4 stroke Rated power 90hp (66.2kW) Rated speed 2200r/min Air filter double Fuel Diesel Fuel tank capacity 150L Clutch Dry-friction, 2 stage, ceramic disc Swing draw bar Yes (tow bar + swing draw bar) Cab Full view cabin with air con Steering power steering Gearbox 16F + 8R shuttle shift Max speed 33km/h Hydraulic output 2 sets rear remotes - 50L/min Suspension 3 point suspension, Cat 3 Lift capacity 2000kg (610mm behind hitch) Remote lift control lever for operator outside of cabin PTO shaft Non-independent type 540/760 r/min 135 Rectangle spline with 6 teeth Front End Loader Model AKS1500 Max lifting height 3710mm (at pivot pin) Dumping height 2720mm Overloading height 3490mm Ground clearance 1780mm Scraping depth 180mm Bucket width 2000mm Bucket width 2000mm Bucket capacity 0.7m3	Height	2880mm
Wheel base 2200mm Min ground clearance 405mm Weight with FEL + ballast 5100kg Engine model YTO LR4M5-23 Type 4 cyl, water cooled, 4 stroke Rated power 90hp (66.2kW) Rated speed 2200r/min Air filter double Fuel Diesel Fuel tank capacity 150L Clutch Dry-friction, 2 stage, ceramic disc Swing draw bar Yes (tow bar + swing draw bar) Cab Full view cabin with air con Steering power steering Gearbox 16F + 8R shuttle shift Max speed 33km/h Hydraulic output 2 sets rear remotes - 50L/min Suspension 3 point suspension, Cat 3 Lift capacity 2000kg (610mm behind hitch) Remote lift control lever for operator outside of cabin PTO shaft Non-independent type 540/760 r/min I35 Rectangle spline with 6 teeth Front End Loader Model AKS1500 Max lifting height 3710mm (at pivot pin) Dumping height 3720mm Overloading height 3490mm Ground clearance 1780mm Scraping depth 180mm Bucket width 2000mm Bucket width 2000mm	Front wheel tread	1400mm
Min ground clearance Weight with FEL + ballast Engine model Type 4 cyl, water cooled, 4 stroke Rated power Rated speed 2200r/min Air filter double Fuel Diesel Fuel tank capacity Clutch Clutch Dry-friction, 2 stage, ceramic disc Swing draw bar Yes (tow bar + swing draw bar) Cab Full view cabin with air con Steering Gearbox 16F + 8R shuttle shift Max speed 33km/h Hydraulic output 2 sets rear remotes - 50L/min Suspension 3 point suspension, Cat 3 Lift capacity 2000kg (610mm behind hitch) Remote lift control lever for operator outside of cabin PTO shaft Non-independent type 540/760 r/min 135 Rectangle spline with 6 teeth Front End Loader Model AKS1500 Max lifting height 3710mm (at pivot pin) Dumping height Cyening Scraping depth 180mm Bucket width 2000mm Bucket capacity 0.7m3	Rear wheel tread	1300 - 1500mm
Weight with FEL + ballast Engine model YTO LR4M5-23 Type 4 cyl, water cooled, 4 stroke Rated power Rated speed 2200r/min Air filter double Fuel Diesel Fuel tank capacity 150L Clutch Dry-friction, 2 stage, ceramic disc Swing draw bar Yes (tow bar + swing draw bar) Cab Full view cabin with air con Steering power steering Gearbox 16F + 8R shuttle shift Max speed 33km/h Hydraulic output 2 sets rear remotes - 50L/min Suspension 3 point suspension, Cat 3 Lift capacity 2000kg (610mm behind hitch) Remote lift control lever for operator outside of cabin PTO shaft Non-independent type 540/760 r/min I35 Rectangle spline with 6 teeth Front End Loader Model AKS1500 Max lifting height 3710mm (at pivot pin) Dumping height 2720mm Overloading height 3490mm Ground clearance 1780mm Bucket width 2000mm Bucket width 2000mm Bucket capacity 0.7m3	Wheel base	2200mm
Engine model Type 4 cyl, water cooled, 4 stroke Rated power 90hp (66.2KW) Rated speed 2200r/min Air filter double Fuel Diesel Fuel tank capacity 150L Clutch Dry-friction, 2 stage, ceramic disc Swing draw bar Yes (tow bar + swing draw bar) Cab Full view cabin with air con Steering power steering Gearbox 16F + 8R shuttle shift Max speed 33km/h Hydraulic output 2 sets rear remotes - 50L/min Suspension 3 point suspension, Cat 3 Lift capacity 2000kg (610mm behind hitch) Remote lift control lever for operator outside of cabin PTO shaft Non-independent type 540/760 r/min I35 Rectangle spline with 6 teeth Front End Loader Model AKS1500 Max lifting height 3710mm (at pivot pin) Dumping height 2720mm Overloading height 3490mm Ground clearance 1780mm Scraping depth Bucket width 2000mm Bucket capacity 0.7m3	Min ground clearance	405mm
Type 4 cyl, water cooled, 4 stroke Rated power 90hp (66.2kW) Rated speed 2200r/min Air filter double Fuel Diesel Fuel tank capacity 150L Clutch Dry-friction, 2 stage, ceramic disc Swing draw bar Yes (tow bar + swing draw bar) Cab Full view cabin with air con Steering power steering Gearbox 16F + 8R shuttle shift Max speed 33km/h Hydraulic output 2 sets rear remotes - 50L/min Suspension 3 point suspension, Cat 3 Lift capacity 2000kg (610mm behind hitch) Remote lift control lever for operator outside of cabin PTO shaft Non-independent type 540/760 r/min I35 Rectangle spline with 6 teeth Front End Loader Model AKS1500 Max lifting height 3710mm (at pivot pin) Dumping height 2720mm Overloading height 3490mm Ground clearance 1780mm Scraping depth 180mm Bucket width 2000mm Bucket width 2000mm	Weight with FEL + ballast	5100kg
Rated power Rated speed Rated	Engine model	YTO LR4M5-23
Rated speed 2200r/min Air filter double Fuel Diesel Fuel tank capacity 150L Clutch Dry-friction, 2 stage, ceramic disc Swing draw bar Yes (tow bar + swing draw bar) Cab Full view cabin with air con Steering power steering Gearbox 16F + 8R shuttle shift Max speed 33km/h Hydraulic output 2 sets rear remotes - 50L/min Suspension 3 point suspension, Cat 3 Lift capacity 2000kg (610mm behind hitch) Remote lift control lever for operator outside of cabin PTO shaft Non-independent type 540/760 r/min I35 Rectangle spline with 6 teeth Front End Loader Model AKS1500 Max lifting height 3710mm (at pivot pin) Dumping height 2720mm Overloading height 3490mm Ground clearance 1780mm Scraping depth 180mm Bucket width 2000mm Bucket capacity 0.7m3	Туре	4 cyl, water cooled, 4 stroke
Air filter Fuel Diesel Fuel tank capacity 150L Clutch Dry-friction, 2 stage, ceramic disc Swing draw bar Yes (tow bar + swing draw bar) Cab Full view cabin with air con Steering power steering Gearbox 16F + 8R shuttle shift Max speed 33km/h Hydraulic output 2 sets rear remotes - 50L/min Suspension 3 point suspension, Cat 3 Lift capacity 2000kg (610mm behind hitch) Remote lift control lever for operator outside of cabin PTO shaft Non-independent type 540/760 r/min 135 Rectangle spline with 6 teeth Front End Loader Model AKS1500 Max lifting height 3710mm (at pivot pin) Dumping height 3720mm Overloading height 3490mm Ground clearance 1780mm Scraping depth 180mm Bucket width 2000mm Bucket capacity 0.7m3	Rated power	90hp (66.2KW)
Fuel tank capacity Fuel tank capacity 150L Clutch Dry-friction, 2 stage, ceramic disc Swing draw bar Cab Full view cabin with air con Steering Gearbox 16F + 8R shuttle shift Max speed 33km/h Hydraulic output 2 sets rear remotes - 50L/min Suspension 3 point suspension, Cat 3 Lift capacity 2000kg (610mm behind hitch) Remote lift control lever for operator outside of cabin PTO shaft Non-independent type 540/760 r/min I35 Rectangle spline with 6 teeth Front End Loader Model AKS1500 Max lifting height 3710mm (at pivot pin) Dumping height 2720mm Overloading height 3490mm Ground clearance 1780mm Scraping depth 180mm Bucket width 2000mm Bucket capacity 0.7m3	Rated speed	2200r/min
Fuel tank capacity Clutch Dry-friction, 2 stage, ceramic disc Swing draw bar Cab Full view cabin with air con Steering Gearbox 16F + 8R shuttle shift Max speed 33km/h Hydraulic output 2 sets rear remotes - 50L/min Suspension 3 point suspension, Cat 3 Lift capacity 2000kg (610mm behind hitch) Remote lift control lever for operator outside of cabin PTO shaft Non-independent type 540/760 r/min I35 Rectangle spline with 6 teeth Front End Loader Model AKS1500 Max lifting height 3710mm (at pivot pin) Dumping height 3490mm Ground clearance 1780mm Scraping depth 180mm Bucket width 2000mm Bucket capacity 0.7m3	Air filter	double
Clutch Dry-friction, 2 stage, ceramic disc Swing draw bar Yes (tow bar + swing draw bar) Cab Full view cabin with air con Steering power steering Gearbox 16F + 8R shuttle shift Max speed 33km/h Hydraulic output 2 sets rear remotes - 50L/min Suspension 3 point suspension, Cat 3 Lift capacity 2000kg (610mm behind hitch) Remote lift control lever for operator outside of cabin PTO shaft Non-independent type 540/760 r/min I35 Rectangle spline with 6 teeth Front End Loader Model AKS1500 Max lifting height 3710mm (at pivot pin) Dumping height 2720mm Overloading height 3490mm Ground clearance 1780mm Scraping depth 180mm Bucket width 2000mm Bucket capacity 0.7m3	Fuel	Diesel
disc Swing draw bar Yes (tow bar + swing draw bar) Cab Full view cabin with air con Steering power steering Gearbox 16F + 8R shuttle shift Max speed 33km/h Hydraulic output 2 sets rear remotes - 50L/min Suspension 3 point suspension, Cat 3 Lift capacity 2000kg (610mm behind hitch) Remote lift control lever for operator outside of cabin PTO shaft Non-independent type 540/760 r/min I35 Rectangle spline with 6 teeth Front End Loader Model AKS1500 Max lifting height 3710mm (at pivot pin) Dumping height 2720mm Overloading height 3490mm Ground clearance 1780mm Scraping depth 180mm Bucket width 2000mm Bucket capacity 0.7m3	Fuel tank capacity	150L
Swing draw bar Cab Full view cabin with air con Steering power steering Gearbox 16F + 8R shuttle shift Max speed 33km/h Hydraulic output 2 sets rear remotes - 50L/min Suspension 3 point suspension, Cat 3 Lift capacity 2000kg (610mm behind hitch) Remote lift control lever for operator outside of cabin PTO shaft Non-independent type 540/760 r/min I35 Rectangle spline with 6 teeth Front End Loader Model AKS1500 Max lifting height 3710mm (at pivot pin) Dumping height 2720mm Overloading height 3490mm Ground clearance 1780mm Scraping depth 180mm Bucket width 2000mm Bucket capacity 0.7m3	Clutch	Dry-friction, 2 stage, ceramic
Cab Full view cabin with air con Steering power steering Gearbox 16F + 8R shuttle shift Max speed 33km/h Hydraulic output 2 sets rear remotes - 50L/min Suspension 3 point suspension, Cat 3 Lift capacity 2000kg (610mm behind hitch) Remote lift control lever for operator outside of cabin PTO shaft Non-independent type 540/760 r/min I35 Rectangle spline with 6 teeth Front End Loader Model AKS1500 Max lifting height 3710mm (at pivot pin) Dumping height 2720mm Overloading height 3490mm Ground clearance 1780mm Scraping depth 180mm Bucket width 2000mm Bucket capacity 0.7m3		disc
Steering power steering Gearbox 16F + 8R shuttle shift Max speed 33km/h Hydraulic output 2 sets rear remotes - 50L/min Suspension 3 point suspension, Cat 3 Lift capacity 2000kg (610mm behind hitch) Remote lift control lever for operator outside of cabin PTO shaft Non-independent type 540/760 r/min I35 Rectangle spline with 6 teeth Front End Loader Model AKS1500 Max lifting height 3710mm (at pivot pin) Dumping height 2720mm Overloading height 3490mm Ground clearance 1780mm Scraping depth 180mm Bucket width 2000mm Bucket capacity 0.7m3	Swing draw bar	Yes (tow bar + swing draw bar)
Gearbox 16F + 8R shuttle shift Max speed 33km/h Hydraulic output 2 sets rear remotes - 50L/min Suspension 3 point suspension, Cat 3 Lift capacity 2000kg (610mm behind hitch) Remote lift control lever for operator outside of cabin PTO shaft Non-independent type 540/760 r/min I35 Rectangle spline with 6 teeth Front End Loader Model AKS1500 Max lifting height 3710mm (at pivot pin) Dumping height 2720mm Overloading height 3490mm Ground clearance 1780mm Scraping depth 180mm Bucket width 2000mm Bucket capacity 0.7m3	Cab	Full view cabin with air con
Max speed 33km/h Hydraulic output 2 sets rear remotes - 50L/min Suspension 3 point suspension, Cat 3 Lift capacity 2000kg (610mm behind hitch) Remote lift control lever for operator outside of cabin PTO shaft Non-independent type 540/760 r/min I35 Rectangle spline with 6 teeth Front End Loader Model AKS1500 Max lifting height 3710mm (at pivot pin) Dumping height 2720mm Overloading height 3490mm Ground clearance 1780mm Scraping depth 180mm Bucket width 2000mm Bucket capacity 0.7m3	Steering	power steering
Hydraulic output 2 sets rear remotes - 50L/min Suspension 3 point suspension, Cat 3 Lift capacity 2000kg (610mm behind hitch) Remote lift control lever for operator outside of cabin PTO shaft Non-independent type 540/760 r/min I35 Rectangle spline with 6 teeth Front End Loader Model AKS1500 Max lifting height 3710mm (at pivot pin) Dumping height 2720mm Overloading height 3490mm Ground clearance 1780mm Scraping depth 180mm Bucket width 2000mm Bucket capacity 0.7m3	Gearbox	16F + 8R shuttle shift
Suspension 3 point suspension, Cat 3 Lift capacity 2000kg (610mm behind hitch) Remote lift control lever for operator outside of cabin PTO shaft Non-independent type 540/760 r/min I35 Rectangle spline with 6 teeth Front End Loader Model AKS1500 Max lifting height 3710mm (at pivot pin) Dumping height 2720mm Overloading height 3490mm Ground clearance 1780mm Scraping depth 180mm Bucket width 2000mm Bucket capacity 0.7m3	Max speed	33km/h
Lift capacity 2000kg (610mm behind hitch) Remote lift control lever for operator outside of cabin PTO shaft Non-independent type 540/760 r/min I35 Rectangle spline with 6 teeth Front End Loader Model AKS1500 Max lifting height 3710mm (at pivot pin) Dumping height 2720mm Overloading height 3490mm Ground clearance 1780mm Scraping depth 180mm Bucket width 2000mm Bucket capacity 0.7m3	Hydraulic output	2 sets rear remotes - 50L/min
Remote lift control lever for operator outside of cabin PTO shaft Non-independent type 540/760 r/min I35 Rectangle spline with 6 teeth Front End Loader Model AKS1500 Max lifting height 3710mm (at pivot pin) Dumping height 2720mm Overloading height 3490mm Ground clearance 1780mm Scraping depth Bucket width 2000mm Bucket capacity 0.7m3	Suspension	3 point suspension, Cat 3
PTO shaft Non-independent type 540/760 r/min I35 Rectangle spline with 6 teeth Front End Loader Model AKS1500 Max lifting height 3710mm (at pivot pin) Dumping height 2720mm Overloading height 3490mm Ground clearance 1780mm Scraping depth 180mm Bucket width 2000mm Bucket capacity 0.7m3	Lift capacity	2000kg (610mm behind hitch)
r/min I35 Rectangle spline with 6 teeth Front End Loader Model AKS1500 Max lifting height 3710mm (at pivot pin) Dumping height 2720mm Overloading height 3490mm Ground clearance 1780mm Scraping depth 180mm Bucket width 2000mm Bucket capacity 0.7m3	Remote lift control lever for operator outside of cabin	
Front End Loader Model AKS1500 Max lifting height 3710mm (at pivot pin) Dumping height 2720mm Overloading height 3490mm Ground clearance 1780mm Scraping depth 180mm Bucket width 2000mm Bucket capacity 0.7m3	PTO shaft	Non-independent type 540/760
Front End Loader Model AKS1500 Max lifting height 3710mm (at pivot pin) Dumping height 2720mm Overloading height 3490mm Ground clearance 1780mm Scraping depth 180mm Bucket width 2000mm Bucket capacity 0.7m3		r/min I35 Rectangle spline with
Model AKS1500 Max lifting height 3710mm (at pivot pin) Dumping height 2720mm Overloading height 3490mm Ground clearance 1780mm Scraping depth 180mm Bucket width 2000mm Bucket capacity 0.7m3		6 teeth
Max lifting height 3710mm (at pivot pin) Dumping height 2720mm Overloading height 3490mm Ground clearance 1780mm Scraping depth 180mm Bucket width 2000mm Bucket capacity 0.7m3	Front End Loader	
Dumping height 2720mm Overloading height 3490mm Ground clearance 1780mm Scraping depth 180mm Bucket width 2000mm Bucket capacity 0.7m3	Model	AKS1500
Overloading height 3490mm Ground clearance 1780mm Scraping depth 180mm Bucket width 2000mm Bucket capacity 0.7m3	Max lifting height	3710mm (at pivot pin)
Ground clearance 1780mm Scraping depth 180mm Bucket width 2000mm Bucket capacity 0.7m3	Dumping height	2720mm
Scraping depth 180mm Bucket width 2000mm Bucket capacity 0.7m3	Overloading height	3490mm
Bucket width 2000mm Bucket capacity 0.7m3	Ground clearance	1780mm
Bucket width 2000mm Bucket capacity 0.7m3	Scraping depth	180mm
		2000mm
	Bucket capacity	0.7m3
	· · ·	1500kg







